

CORS-415

Outdoor Power Cabinet with Battery Shelf
-53.3VDC / 10A Output

Product Features:

- Wall Mount Type
- Battery Charger and Monitor
- Full Featured Status and Alarms
- TCP/IP(Ethernet)
- IP55 Grade
- TEC (Thermo Electric Cooler) for Battery



Input Specifications:

VOLTAGE	1Ø220VAC (176VAC ~ 264VAC)
FREQUENCY	47-63Hz
INRUSH	20A @ 220VAC(Max Cold Start) per Module
CURRENT	4.0A @ 220VAC(Max Continuous) per Module
PROTECTION	Double pole 10A Fuse / 250VAC per Module
LEAKAGE	3.5mA Max @ 264VAC
EFFICIENCY	92% Typical
HARMONICS	EN61000-3-2 Class D Compliant (>98PF)
PROTECTION	Input Under voltage, Overvoltage

Output Specifications:

Vout	-53.3VDC
Iout	10Amax
ADJUSTMENT RANGE	-40VDC~-58VDC
LINE REGULATION	±0.5% Max over entire input range
LOAD REGULATION	±0.5% Maximum
TEMP REGULATION	±0.5% Maximum
RIPPLE	≤ 250mVp-p(10Hz~14MHz)
SETPOINT ACCURACY	±0.5%
OVER CURRENT	105~130%
OVER VOLTAGE	-59VDC(recycle input to reset)
PROTECTION	Thermal Shutdown Battery Temp. Compensation

Status & Control signals:

DC OK	High Signal indicates DC Output is on and within regulation
INTERFACE	Dry Contact(4Ports) : Normal Open TCP/IP (Ethernet)

General Specifications:

OPERATING TEMP	-30 °C to +50 °C
STORAGE TEMP	-40 °C to +85 °C
OPERATING HUMIDITY	10% to 90% (Non-Condensing)
STORAGE HUMIDITY	5% to 95% (Non-Condensing)
COOLING	Convection cooling
VIBRATION	10-55Hz, 2G, 3min period/60 min each(3 axes)
SHOCK	20G Peak Acceleration
RELIABILITY	150,000 Hrs MTBF
ALTITUDE	0~10,000 Feet
SIZE(W×D×H)	260 × 220 × 650mm

Electromagnetic Compatibility:

EMISSIONS	EN55022 Level A (Conducted)
ELECTROSTATIC DISCHARGE	EN61000-4-2, 4KV Contact / 8KV Air
RADIATED SUSCEPTIBILITY	EN61000-4-3, 26-1000MHz, 10V/M, 80%AM
EFT/BURSTS	EN61000-4-4, 2KV
SURGE	EN61000-4-5
CONDUCTED IMMUNITY	EN61000-4-6, 0.15-800MHz, 10V 80%
VOLTAGE DIPS	EN61000-4-10, 95% Dip&10ms, 30% Dip&500ms
VOLTAGE INTERRUPTIONS	EN61000-4-11, 95% reduction, 5ms
FLUCTUATIONS & FLICKER	EN61000-3-3

Standards & Approvals: TBD

UL/CUL	60950-1
CE MARK	Low Voltage Directive
TELCORDIA	Nebs Compliant (Level3)

Outdoor Power Cabinet with Battery Shelf

-53.3VDC / 10A Output

CORS-415

Outline Drawing:

