

KLTE-430

Outdoor Power Cabinet with Battery
-54.0VDC / 30A Output



Product Features:

- Wall Mount Type
- Battery Charger and Monitor
- Full Featured Status and Alarms
- Dry Contact Alarm
- IP55 Grade

Input Specifications:

VOLTAGE	1Ø220VAC (176VAC ~ 264VAC)
FREQUENCY	47-63Hz
INRUSH-CURRENT	20A @ 220AVC (Max. Cold Start)
PROTECTION	Double pole 15A Fuse / 250Vac
LEAKAGE	3.5mA Max @ 264Vac
EFFICIENCY	92% Typical
HARMONICS	EN61000-3-2 Class D Compliant (>98PF)
PROTECTION	Input Under & Overvoltage
BATTERY	12V/18AH * 4Cell

Output Specifications:

Vout	-53.3VDC
Iout	30Amax
ADJUSTMENT RANGE	-40VDC~-58VDC
LINE REGULATION	±0.5% Max over entire input range
LOAD REGULATION	±0.5% Maximum
TEMP REGULATION	±0.5% Maximum
RIPPLE	≤ 250mVp-p(10Hz~14MHz)
SETPOINT ACCURACY	±0.5%
OVER CURRENT	105~130%
OVER VOLTAGE PROTECTION	-59VDC(recycle input to reset) Thermal Shutdown Battery Temp. Compensation

Status & Control signals:

COMMUNICATION INTERFACE	RS485, TCP/IP Output alarms
-------------------------	--------------------------------

General Specifications:

OPERATING TEMP	-30°C to +50°C
STORAGE TEMP	-40°C to +85°C
OPERATING HUMIDITY	10% to 90% (Non-Condensing)
STORAGE HUMIDITY	5% to 95% (Non-Condensing)
COOLING	Convection cooling
RELIABILITY	150,000 Hrs MTBF
ALTITUDE	2,000Meter
SIZE(W×D×H)	400 × 246 × 650mm(Rectifier)

Electromagnetic Compatibility:

EMISSIONS	EN55022 Level A (Conducted)
ELECTROSTATIC DISCHARGE	EN61000-4-2, 4KV Contact / 8KV Air
RADIATED SUSCEPTIBILITY	EN61000-4-3, 26-1000MHz, 10V/M, 80%AM
EFT/BURSTS	EN61000-4-4, 2KV
SURGE	EN61000-4-5
CONDUCTED IMMUNITY	EN61000-4-6, 0.15-800MHz, 10V 80%
VOLTAGE DIPS	EN61000-4-10, 95% Dip&10ms, 30% Dip&500ms
VOLTAGE INTERRUPTIONS FLUCTUATIONS & FLICKER	EN61000-4-11, 95% reduction, 5ms EN61000-3-3

Standards & Approvals: TBD

UL/CUL	60950-1
CE MARK	Low Voltage Directive
TELCORDIA	Nebs Compliant (Level3)

KLTE-430

Outdoor Power Cabinet with Battery
-54.0VDC / 30A Output

Outline Drawing:

