

Power Supply Unit type AC/DC Converter

L7SA

+30V/55W, +12V/65W, +5.5V/35W

HIGHLIGHTS

- Modular design for accommodating small size applications and easy maintenance
- Plug and play
- Isolated Output
- Natural air convection cooling
- Application : KDDI LTE Pico



GENERAL SPECIFICATIONS

INPUT

- Voltage.....+100VDC
- Efficiency ≥ Typically 81%

OUTPUT

- Nominal output(Ch1) +30V/55W
- Nominal output(Ch2) +12V/65W
- Nominal output(Ch3) +5.5V/35W
- Ripple & Noise ≤ 50/120/300mVp-p
(20MB/W SCOING)

ENVIRONMENT

- Operating Temperature.....-40°C ~ +100 °C
- Operating Relative Humidity.....5% ~ 95%
- Storage Temperature.....-40°C ~ +85 °C
- Storage Relative Humidity.....5% ~ 95%

FUNCTION

- Input Low · High Voltage Protection
- Output Over Voltage Protection
- Output Over Current Protection(at Load 110~130%)
- Output Short Protection
- Load Sharing (±5%)
- Remote Feed Back

PHYSICAL DIMENSIONS(W×D×H)

- 208 × 143 × 40 (mm)

AGENCY COMPLIANCES

- Standard – IEC CISPR Pub22 Class A
FCC Part15 Class A