

## LOPU-A2R

### 29V/24A, AC/DC Power

#### Product Features:

- IP65 design for indoor or outdoor installations
- International Safety Approvals
- Cooling by free air convection
- High efficiency & reliability



## GENERAL SPECIFICATIONS

### INPUT

- Voltage..... 220Vac
- Range..... 176 ~ 264 Vac
- Inrush ..... ≤ 40A
- Efficiency ..... ≥ Typically 90%

### OUTPUT

- Voltage..... Default 29.0VDC
- Current..... 24Amax
- Ripple & Noise ..... ≤ 250mVp-p
- Line & Load Regulation ..... ≤ ± 1%

## PROTECTION & FUNCTION

- Output Over Voltage (Auto Reset)
- Output Current Limit (Auto recovery)
- Output Short Circuit (Auto recovery)
- Thermal (Auto recovery)
- Hold Up –Time(50mS)
- Dynamic regulation (±5%)

## PHYSICAL DIMENSIONS(W×D×H)

- 239×319 ×112(mm)

## ENVIRONMENT

### OPERATION

- Temperature..... -30°C ~ +50 °C (Full Power)
- Relative Humidity..... 5% ~ 95%

### NON-OPERATION

- Ambient Temperature..... -40°C ~ +85 °C
- Relative Humidity..... 5% ~ 95%(non-condensing)

## AGENCY COMPLIANCES

- EN 50022 Class-A
- IEC 61000 4-5
- IEC 60950-1/ IEC 60950-22

