

LOPU-A4M

48V/23A, AC/DC Power

Product Features:

- IP65 design for indoor or outdoor installations
- International Safety Approvals
- Cooling by free air convection
- High efficiency & reliability



GENERAL SPECIFICATIONS

INPUT

- Voltage..... 100Vac
- Range..... 85 ~ 132 Vac
- Inrush ≤ 40A
- Efficiency ≥ Typically 90%

OUTPUT

- Voltage..... Default 48.0VDC
- Current..... 23Amax
- Ripple & Noise ≤ 250mVp-p
- Line & Load Regulation ≤ ± 1%

PROTECTION & FUNCTION

- Output Current Limit (Auto recovery)
- Output Short Circuit (Auto recovery)
- Thermal (Auto recovery)
- Hold Up –Time(20mS)
- Dynamic regulation (47V~49V)

PHYSICAL DIMENSIONS(W×D×H)

- 441×218 ×120(mm)

ENVIRONMENT

OPERATION

- Temperature..... -30°C ~ +50 °C (Full Power)
- Relative Humidity..... 5% ~ 95%

NON-OPERATION

- Ambient Temperature..... -40°C ~ +85 °C
- Relative Humidity..... 5% ~ 95%(non-condensing)

AGENCY COMPLIANCES

- VCCI Class-B
- IEC 61000 4-5
- IEC 60950-1/ IEC 60950-22