

## NORS-4150

Outdoor Power Cabinet with Battery Shelf  
-54VDC / 150A Output



### Product Features:

- Outdoor Rectifier system
- Modular design for accommodating high power applications and easy maintenance
- N+1 Redundancy
- Low voltage Battery disconnection

### Input Specifications:

VOLTAGE	1Ø3W220VAC (±20%)
FREQUENCY	47-63Hz
INRUSH	30A @ 220VAC(Max Cold Start) per Module
PROTECTION	Double pole 63A Fuse / 250VAC per Module
LEAKAGE	3.5mA Max @ 220VAC per Module
EFFICIENCY	90% Typical
PROTECTION	Input Under voltage, Overvoltage

### General Specifications:

OPERATING TEMP	-30 °C to +50 °C
STORAGE TEMP	-40 °C to +75 °C
OPERATING HUMIDITY	5% to 90% (Non-Condensing)
STORAGE HUMIDITY	5% to 95% (Non-Condensing)
COOLING	DACS
RELIABILITY	100,000 Hrs MTBF
SIZE(W×D×H)	650 × 700 × 1850mm

### Output Specifications:

Vout	-54.0VDC / +27.0VDC
Iout	150Amax(-54V) +( 40Amax(+27V))
ADJUSTMENT RANGE	-43VDC~-58VDC
LINE REGULATION	±1.0% Max over entire input range
LOAD REGULATION	±1.0% Maximum
RIPPLE	≤ 250mVp-p(10Hz~14MHz)
OVER CURRENT	105~130%
OVER VOLTAGE	-59.5VDC±0.5V
PROTECTION	Thermal Shutdown Battery Temp. Compensation

### Electromagnetic Compatibility:

ELECTROSTATIC	KN24/IEC 61000-4-2
EFT/BURSTS	KN24/IEC 61000-4-4
SURGE	KN24/IEC 61000-4-5
VOLTAGE DIPS	KN24/IEC 61000-4-11
VOLTAGE INTERRUPTIONS	KN24/IEC 61000-4-11

### Status & Control signals:

DC OK	High Signal indicates DC Output is on and within regulation
INTERFACE	Dry Contact(2Ports) : Normal Open

### Status & Control signals:

KC	KN22/24
----	---------

